



This Hoshizaki IM-240DNE is a stackable cube ice maker producing up to 240 kg of high-quality cube ice per 24 hours. Meeting even the strictest hygiene requirements, this true allrounder offers many application possibilities in segments including the foodservice and medical sector. All Cubers are equipped with an electronic control system. This ensures an optimized ice-making process, even under varying circumstances. Without additional manual assistance or adjustments required, our Cubers produce generous amounts of ice cubes, at a consistently high quality.

The IM-240DNE uses refrigerant R404A.

Material

The exterior is made of stainless steel. The closed water circuit provides maximum protection against any type of contamination during the entire cubing process. All Hoshizaki machines are easy to use, clean, and maintain.

Unique Technology

A dedicated jet of fresh water is injected into each of the closed cells. Excess water leaves the closed cell through a set of outlets. The cell walls block the freezing water's expansion from all sides while reaching down to -30°C during the cubing process. Thanks to the automatic rinse cycles, impurities such as minerals, are eliminated from the water resulting in the purest ice possible while your machine is protected from calcification and mineral build-up.

Smart Design

Like all Hoshizaki Ice makers, the IM-240DNE is designed to last and comes with smart design extras such as a magnetic water pump without direct coupling. This element prevents leakage from the water circuit and improves the life expectancy of the machine.

Perfect Fit

Need to amp up your production capacity? These ice makers can be stacked and combined with modular bins and bases. This allows the user to mix and match depending on individual requirements, ice consumption, and space conditions. The dimensions of the IM-240DNE are 1084 x 700 x 500 mm.

Plug&Play

The smart plug-and-play design guarantees an easy and quick set-up.



SPECIFICATIONS

Product title	Cuber, Modular & Stackable	CO2 equivalent (kg)	1.882
Production Capacity (kg/24h) approx. (AT 10°C, WT 10°C)	240	Cooling System	Air Cooled
Power supply	1/220 - 240V/50Hz	Product configuration	Stackable
Electric Consumption (kW)	1,33	Net weight (kg)	88
Dimensions W x D x H (mm), legs excluded	1084 x 700 x 500	Gross Weight Packed (kg)	101
Ice type	Large cubes, Standard	Corresponding bin(s)	F_1025_52S, F_600_42S, F_650_44S, F_950_48S
Refrigerant	R404A		