Project	
Rev.:	
Zone:	
Location:	



CODICE **CR1015839** 

MODELLO

Q90PCF/E801

SERIE

QUEEN 9

#### **GENERAL CHARACTERISTICS**

It is the choice of those who need maximum strength and power. Queen9 is distinguished by its 900 mm depth, a 20/10-thick work surface, double-crown burners, and the use of elegant stainless steel with a Scotch Brite finish.

Details that not only offer maximum functionality and aesthetics, but also take into account the practical and ergonomic needs of those who work.

The extreme freedom of composition allows top models to be combined with accessorizable oven and neutral base units, even with hygienic finishes.

With more than 350 models immediately available in the catalog, Queen9 is already ready to start giving its best.

In addition, all equipment that makes up a Queen9 kitchen is certified in compliance with international standards, including CE, GAR, AGA and others.



### **TECHNICAL SPECIFICATIONS**

All-molded hob made from a single sheet of thick stainless steel. Cast-iron radiant plates, fixed watertight to eliminate any liquid infiltration on electrical wiring.

6-position, ergonomic, recessed and tilted power output knobs. Warning lights indicating "plates under tension."

Electric oven

Groups of stainless steel heating elements placed on the ceiling and under the sole of the firing chamber.

Thermostatic temperature control in the chamber from 100°C to 300°C. Warning light indicating "equipment under voltage."

 $Indicator\ light\ indicating\ that\ the\ set\ temperature\ has\ been\ reached.$ 

The temperature is adjusted by means of a 7-position selector switch, and a warning light indicating the activation of the heating is located on the dashboard.

Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and under-knobs can be washed at the end of the working day without compromising functionality and safety.

The front bar is a comfortable foothold for the cook; it keeps a safe distance from the worktop and thus protects against accidental collisions with what is resting on the worktops and at the same time the handles.

Project	
Rev.:	
Zone:	
Location	



CODICE **CR1015839** 

MODELLO

Q90PCF/E801

SERIE
QUEEN 9

## Technical Information

SPECIFICATION	DATA
MATERIAL	CR1015839
DEFINITION	Q90PCF/E801 4 P.EL.Q. F/ELETTRICO
COMMERCIAL LINE	QUEEN
SUPPLY	ELECTRICS
DIM. WIDTH	800 mm
DIM. PRODUCTIVITY	900 mm
DIM. HEIGHT	870 mm
NET WEIGHT	162 Kg
VOLUME (net)	0.626
PACKAGE LENGTH	840 mm
PACKAGE WIDTH	1020 mm
PACKAGING HEIGHT	1170 mm
PACKAGE VOLUME	1,003 m3
GROSS PACKING WEIGHT	174 Kg
STANDARD POWER SUPPLY	380-415V 3N
FREQUENCY	50-60 Hz
ELECTRICAL POWER	22 kW
N. FIRES/PLATES	QUATTRO FUOCHI
IP GRADE	IPX4
CERTIFIED MODEL	Q90PCF/E801

Project	
Rev.:	
Zone:	
ocation:	



CODICE **CR1015839** 


MODELLO

Q90PCF/E801

SERIE
QUEEN 9

SCHEMA DI INSTALLAZIONE - INSTALLATION DIAGRAM - INSTALLATIONSPLAN - SCHÉMA D'INSTALLATION -ESQUEMA DE INSTALACION -INSTALLATIESCHEMA - IINSTALLATIONSRITNINGAR

MISURE IN cm - DIMENSIONS IN cm - ABMESSUNGEN IN cm-MESURES EN cm MEDIDAS EN cm - MATEN IN cm - DIMENSIONES EN cm



E	Pressacavo entrata linea elettrica - Stopfbuchse - Electric cable stress relief - Presse étoupe de câble él - Pisacable - Elektrische kabelwartel - Entrada cabo eléctrico	G	Arrivo gas - Gasanschluss - Gas connection - Arrivée gaz - Union de gas - Gasaansluiting - Ligação gás
S	Attacco scarico acqua - Wasserablauf - Water outlet - Vidange de l'eau - Desaguadero - Wateraftapaansluiting - Junção descarga água	H20	Arrivo acqua - Wasseranschluss - Water inlet - Arrivée eau - Union de agua - Wateraansluiting - Junção alimentação áqua
S1	Scarico vasca - Wannenabflussrohr - Pan outlet - Vidange du bac - Descarga cuba - Water toevoer - Descarga da cuba	A1 = A2 =	Calda - Heiss - Warm - Chaude - Caliente - Warm - Morno
S2	Valvola di depressione - Anti-depression valve - Unterdruck ventil - Soupape de dépression - Válvula de dépresión - Onderdrukklep - Válvula de depressão		
S3	Scarico acqua intercapedine - Wasserablauf Zwischenraum - Jacket water drain Evacuation eau double envelope - Descarga de agua intersticios - Afvoer water tussenruimte - Descarga de água na	L	Rubinetto di livello - Level tap - Wasserhahn - Robinet de
<b>S4</b>	marmita com Sistema de aquecimento indirecto  Scarico - Abflussrohr - Drain - Tuyau d'évacuation -	-	niveau - Grifo de nivel - Niveaukraan - Torneira de nivel
	Tubo de drenaje - Aftapbuis - Tubulação de dreno		

14



CODICE **CR1015839** 

MODELLO

Q90PCF/E801

SERIE
QUEEN 9

# PRODUCT'S RANGE PLUS



The front bar is a comfortable foothold for the cook; it keeps a safe distance from the worktop and thus protects against accidental collisions with what is resting on the worktops and at the same time the handles.



Square plates of 30x30 each, fixed watertight on the worktop.



The temperature is adjusted by means of a 7-position selector switch, and a warning light indicating the activation of the heating is located on the dashboard.



Thanks to the jet-proofing certification (IPX5) obtained through specific tests, knobs and underknobs can be washed at the end of the working day without compromising functionality and safety.

